

## PRODUCT INFORMATION

# LM800

## DESCRIPTION

Waterproof GREEN masking tape.



## APPLICATION

Waterproof masking tape is widely used for car repair applications as well as for wall painting on building and construction sites and industrial use.

## PRODUCT DATA

Backing  
Adhesive

63g/m<sup>2</sup> Saturated Crepe Paper; Green  
Natural Rubber and Resins Solvent Based

	UNITS	TEST METHOD
Total Thickness	0.130mm	PSTC 133
Adhesion to Steel	4.8N/25mm	PSTC 101
Tensile Strength MD	90N/25mm	PSTC131
Elongation at Break	8%	PSTC 131
Temp. Resistance	120°C (30 min@90)	

## FEATURES

Natural rubber solvent based adhesive.

Saturated Crepe Paper backing.

## BENEFITS

- Good adhesion even on uneven surfaces.
- Easy removal, if removed as soon as paint is dry, without adhesive residue.
- Heat Resistant up to 120°C, (30 minutes @ 90°C)
- Well comfortable to most shaped surfaces.
- Compatible with most paints and lacquers.
- Removable without breaking.
- Hand Tearable.
- Highly resistant to moisture and water.

## CONDITIONS OF USE AND CONFORMITY

Suggested storage in dry area away from direct sunlight temperature should range from 15°C to 25°C with max relative humidity of 65%. Tape and Jumbo Roll should be used respectively within 12 months and 6 months from date of manufacture.

All technical information and data above mentioned and provided are to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The technical information and other statements contained in this document have been compiled for your guidance and usage. It is the users sole responsibility to determine the suitability of the product in actual application under specific conditions.