according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version	Revision Date:	SDS Number:	
1.0	05.07.2018	H55880	
SECTION 1:	Identification of the substant	e/mixture and of the company/undertaking	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	1.1	Product	identifier
------------------------	-----	---------	------------

on use

Trade name : ANTIGRAFFITI ADDITIVE

1.2 Relevant identified uses of the substance or mixture and uses advised against

only.

Use of the Substance/Mixture	:	Additive, Paint
Recommended restrictions	:	For use in industrial installations or professional treatment

1.3 Details of the supplier of the safety data sheet

Company	:	Roberlo s.a. Ctra. Nacional II, Km. 706,5 17457 Riudellots de la Selva Spain
Telephone	:	+34972478060
Telefax	:	+34972477394
E-mail address of person responsible for the SDS	:	msds@roberlo.com

1.4 Emergency telephone number

+34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	72/2008)
Flammable liquids, Category 3	H226: Flammable liquid and vapour.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms

2



Warning

Hazard statements

: H226 Flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
Precautionary :	statements :	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
		Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.
Additional Lat EUH208	•	yl methacrylate. May produce an allergic reaction.
2.3 Other hazards		

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
isobutyl methacrylate	97-86-9 202-613-0 607-113-00-X 01-2119488331-38	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400	>= 0.25 - < 1
2-methoxypropyl acetate	70657-70-4 274-724-2 607-251-00-0	Flam. Liq. 3; H226 Repr. 1B; H360D STOT SE 3; H335	>= 0.1 - < 0.3
Substances with a workplace exposure limit :			
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226	>= 70 - < 90

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version	Revision Date:	SDS Number:
1.0	05.07.2018	H55880

SECTION 4: First aid measures

4.1 Description of first aid measures			
General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.	
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.	
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.	
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.	
4.2 Most important symptoms ar	nd e	effects, both acute and delayed	
Symptoms	:	Inhalation may provoke the following symptoms: Headache Dizziness Fatigue Weakness Skin contact may provoke the following symptoms: Redness Pain Ingestion may provoke the following symptoms: Abdominal pain Nausea Vomiting Diarrhoea	
4.3 Indication of any immediate	mer	lical attention and special treatment needed	

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Ver 1.0		vision Date: 07.2018	SDS Number: H55880
	Unsuitable extinguisl media	hing :	High volume water jet
5.2	Special hazards aris	ing from the	e substance or mixture
	Specific hazards dur firefighting	ing :	Do not allow run-off from fire fighting to enter drains or water courses.
	Hazardous combusti products	on :	No hazardous combustion products are known
5.3 Advice for firefighters		rs	
	Special protective ec for firefighters	quipment :	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

· / ·	
Personal precautions :	Remove all sources of ignition.
·	Evacuate personnel to safe areas.
	Beware of vapours accumulating to form explosive
	concentrations. Vapours can accumulate in low areas.
6.2 Environmental precautions	
Environmental precautions :	Prevent product from entering drains.
	Prevent further leakage or spillage if safe to do so.
	If the product contaminates rivers and lakes or drains inform
	•
	respective authorities.
6.3 Methods and material for conta	inment and cleaning up
Methods for cleaning up :	Contain spillage, and then collect with non-combustible
	absorbent material, (e.g. sand, earth, diatomaceous earth,
	vermiculite) and place in container for disposal according to

6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

local / national regulations (see section 13).

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version	Revision Date:	SDS Number:
1.0	05.07.2018	H55880

SECTION 7: Handling and storage

7.1 Precautions for safe handling	g	
Advice on safe handling	:	 Avoid formation of aerosol. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Hygiene measures	:	Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage,	inc	luding any incompatibilities
Requirements for storage areas and containers	:	No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Storage period	:	12 Months
Further information on storage stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	For the use of this product do not exist particular recommendations apart from that already indicated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1- methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m3	2000/39/EC

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version	Revision Date:	SDS Number:
1.0	05.07.2018	H55880

Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm	GB EH40
			274 mg/m3	
Further information		Can be absorbed through skin. The assigned substances are those for which		
	there are con	there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	100 ppm	GB EH40
			548 mg/m3	
Further information	Can be absorbed through skin. The assigned substances are those for which			
	there are con	there are concerns that dermal absorption will lead to systemic toxicity.		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3

8.2 Exposure controls

Personal protective equipr	Personal protective equipment		
Eye protection	Eye wash bottle with pure wate Tightly fitting safety goggles	r	
Hand protection Material	Solvent-resistant gloves		
Skin and body protection	Impervious clothing Choose body protection accord concentration of the dangerous		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid, viscous
Colour	:	colourless
Odour	:	characteristic
рН	:	not determined
Melting point/range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	42 °C Method: ISO 1523, closed cup Setaflash
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower	:	not determined

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
flammability lin	nit	
Vapour pressu	re :	not determined
Density	:	0.990 g/cm3 (20 °C) Method: ISO 2811-1
Solubility(ies) Water solub	bility :	immiscible
Viscosity		
Viscosity, d	ynamic :	28 mPa.s (20 °C) Method: ISO 2555
Viscosity, k	inematic :	> 20.5 mm2/s (40 °C)
9.2 Other informat	ion	
No data availa	ble	
SECTION 10: Sta	bility and reactive	vity
10.1 Reactivity		
No decomposi	tion if stored and ap	oplied as directed.
10.2 Chemical stal	oility	
No decomposi	tion if stored and ap	oplied as directed.
10.3 Possibility of	hazardous reaction	ons
Hazardous rea	ctions :	No decomposition if stored and applied as directed.
		Vapours may form explosive mixture with air.
10.4 Conditions to	avoid	
Conditions to a	avoid :	Heat, flames and sparks.
10.5 Incompatible	materials	
Materials to av		No data available
10.6 Hazardous de No data availa		lucts
SECTION 11: To:	xicological infor	mation
11.1 Information o	n toxicological eff	fects
Acute toxicity	-	
Components:		
2-methoxy-1-r	methylethyl acetat	te:

Acute oral toxicity : LD50 Oral (Rat): 8,532 mg/kg

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
		Method: OECD Test Guideline 401
Acute ir	nhalation toxicity :	LC50 (Rat): 35.7 mg/l Exposure time: 4 h Test atmosphere: gas Method: OECD Test Guideline 403
Acute d	ermal toxicity :	LD50 (Rat): 5,000 mg/kg Method: OECD Test Guideline 402
Further	· information	

Product:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-methoxy-1-methylethyl acetate:

Toxicity to fish	:	LC50 (Fish): 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): 408 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Algae): 1,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
12.6 Other adver	se effects	
Product: Additional ec information	ological :	No data available
SECTION 13: D	isposal considera	ations
13.1 Waste treat	ment methods	
Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminate	d packaging :	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
SECTION 14: T	ransport information	tion
14.1 UN number		
IMDG	:	UN 1263
IATA (Cargo) :	UN 1263
14.2 UN proper s	hipping name	
ADR	:	PAINT RELATED MATERIAL
IMDG	:	PAINT RELATED MATERIAL
IATA (Cargo) :	Paint related material
14.3 Transport h	azard class(es)	

ADR IMDG IATA (Cargo)	:	3 3 3
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels		III F1 30 3
IMDG Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>
IATA (Cargo)		

9/12

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
aircraft)		: 366 : Y344 : III : Flammable Liquids
14.5 Environmental hazards		
ADR Environme	ntally hazardous :	: no
IMDG Marine poll	utant :	: no
14.6 Special pr Not applica	ecautions for user	
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code		

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t

Other regulations:

The product is classified and labelled in accordance with EC directives or respective national laws.

15.2 Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

SECTION 16: Other information

Full text of H-Statements

H226 :	Flammable liquid and vapour.	
H315 :	Causes skin irritation.	
H317 :	May cause an allergic skin reaction.	
H319 :	Causes serious eye irritation.	
H335 :	May cause respiratory irritation.	
H360D :	May damage the unborn child.	
H400 :	Very toxic to aquatic life.	
Full text of other abbreviations		

:	Acute aquatic toxicity
:	Eye irritation
:	Flammable liquids
:	Reproductive toxicity
:	Skin irritation
	:

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version 1.0	Revision Date: 05.07.2018	SDS Number: H55880
Skin Sens.	:	Skin sensitisation
STOT SE 2000/39/EC	:	Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40 2000/39/EC / T 2000/39/EC / S GB EH40 / TW GB EH40 / STE	WA : STEL : A :	UK. EH40 WEL - Workplace Exposure Limits Limit Value - eight hours Short term exposure limit Long-term exposure limit (8-hour TWA reference period) Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very **Bioaccumulative**

Further information

Sources of key data used to : http://echa.europa.eu, http://eur-lex.europa.eu compile the Safety Data Sheet

Classification of the mixture:

Flam. Liq. 3

H226

Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

according to Regulation (EC) No. 1907/2006



ANTIGRAFFITI ADDITIVE

Version	Revision Date:	SDS Number:
1.0	05.07.2018	H55880

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN