

DEFINITION

AIRCOLOR PREFILL SOLVENT BASED is a refillable aerosol for solvent-based paint. Pre-filled with 275ml propellant, solvent and additives, it has the capacity for 100ml of undiluted **DICROM**. This is filled with an aerosol filling machine which produces a ready to use product. Slight colour differences may occur. Always check the colour before application. It can be applied either for spot repairs or refinishing parts.





A compatibility test is recommended to ensure suitability to the substrate. Be aware that if using 2k paints, the pot life is limited.

AIRCOLOR PREFILL SB has a transversal nozzle allows the direction of application to be adjusted by the output nozzle (horizontal/vertical).

PHYSICAL CHARACTERISTICS

Propellant:	DME	
Specific weight:	0,7 kg/l a 20°C	
Extrusion Speed:	1,8 ± 0,4 g/s	
Aerosol Pressure:	4,5 ± 0,5 bar a 25°C	
VOC:	713 g/l	Application 2004/42/EC - IIB (e)(840)


APPLICATION METHOD

			
Nozzle kind: Transversal Red / Black	1 min	15-20 cm	Add 100 ml to the undiluted paint DICROM

REMARKS

Area must be clean, dry and free of grease and dust
Shake the aerosol before use for 1 minutes.
Protect the areas that will not be painted.
Carry out test spray.
Spray several thin coats at the recommended distance.
Drying time depends on type of paint, film thickness of the coating and the temperature.
Re-coatable with 1K or 2k clear coats.

EQUIPMENT CLEANING



*After use, turn
can upside
down and
spray for
several
seconds*

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +10°C and +25°C with relative air humidity of maximum 60%.

SHELF LIFE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.