

## EXTRA FILLER SPOT PRIMER LIGHT GREY OR DARK GREY

### Technical Information



Use Le'Mix Primer as a pre-treatment for painting your car. The primer is fast-drying and suitable for both treated and untreated surfaces including wood, metal, aluminium, glass and stone. The primer offers excellent coverage and filling properties and prevents rust. It is easy to sand, both wet and dry (from grain 400) and can be resprayed with all paints.

### Physical & chemical data

- Base:
  - ◊ Acrylic resin
  - ◊ Nitrocombi resin
- Colourname:
  - ◊ Dark grey
  - ◊ Light grey
- Efficiency:
  - ◊ 500 ML – 1.5 - 2 m<sup>2</sup>
  - ◊ 500 ML – 1.5 - 2 m<sup>2</sup>
  - ◊ 150 ML – 0.5 m<sup>2</sup>
- Dry to touch:
  - ◊ 10 -20 min
  - ◊ 10 - 20 min
- Dust dry:
  - ◊ 5-10 min
  - ◊ 5 - 10 min
- Completely dry: 120 min
- Overcoatable: 120 min
- Surfaces: Wood, metal, aluminium, stone
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
  - ◊ 3500/20 bar
  - ◊ 13/20 bar
  - ◊ 8300/20 bar
- Flash point: 27 °C
- Temperature Resistance:
  - 110 °C
- Storage stability:
  - ◊ 10 y
  - ◊ 5 y
  - ◊ 1.5 y
- Content:
  - ◊ 500 ML
  - ◊ 12 ML
  - ◊ 150 ML

### Quality & properties

- Excellent coverage and filling property
- Easy to sand, both wet and dry (from grain 400)
- Corrosion preventive
- Re-sprayable with all lacquer systems
- Fast drying

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the primer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

Le'Mix Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

For any further technical questions call **Le'Mix + 61 02 97084959** from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

Refer to SDS for all safety , handling , transport and chemical ingredients