

1K ETCH PRIMER

TECHNICAL DATA SHEET



DESCRIPTIONS

Le'Mix 1K Etch Primer / Weld through -anti-corrosion primer has excellent adhesive properties, especially on polished metal, e.g. steel plate. Active rust protection pigments ensure optimum corrosion protection.

Quick drying. Can also be used as a welding primer.

Basis of binder: NC

Colour: red brown

Smell: solvent

Efficiency: 1 m²

Substrate: Sanded: blank metall, cured paintings, primer for refinishing parts, polyester substrates, aluminium.

Temperature resistance: to 90 °C

Storage stability: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

Size: Aerosol cans, maximum nominal volume 400 ml

VOC value: 270,5g

QUALITY AND PROPERTIES

1K acid primer, welder primer

Can be used for spot repairs and refinishing parts

Simple, time-saving application

Fast drying time

Excellent corrosion protection

Very good adhesion, especially on bare sanded metal.

USE INSTRUCTIONS

1-2 coats, when used as a primer

After airing for 10-50 minutes (20 °C) can be top coated.

One light coat when used as a welding primer.

Remove all rust damaged area, clean surface thoroughly and sand.


Area must be dry and free of grease and dust.

Shake the can well for 2 minutes

Carry out test spray




2 min



approx. 15 cm



1-2 C = 10-20 µ



20°C=10-15 min



5 sec

Environmentally compatible: Le'Mix Pty Ltd is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse"

DISCLAIMER OF LIABILITY

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Le'Mix Pty Ltd is not responsible for any misuse or mishandling and therefore will not accept any liability.