

GLOSS WHITE

TECHNICAL DATA SHEET



DESCRIPTIONS

Le'Mix gloss white is an acrylic paint with high opacity, UV resistance and fast drying.
Suitable for all car parts and industrial use, indoors or outdoors.

QUALITY AND PROPERTIES

- High-grade quality acrylic lacquer
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- High surface hardness and good elasticity

PHYSICAL AND CHEMICAL DATA


- Basis of the binder: acrylic resin
- Colour: white
- Smell: solvent
- Glossy: 80-85 gloss unit
- Efficiency: 12ml for several applications
- Drying time (at 20°C, 50% relative air humidity)
- Dust-dry: after approx. 15 minutes
- Dry to touch: after approx. 60 minutes
- Dust-dry: after approx. 5-10 minutes
- Tack-free: after approx. 10-20 minutes
- Coatable: after approx. 2 hours
- Storage stability: 10 years, if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- Size: aerosol 400ml

USE INSTRUCTIONS


The surface has to be clean, dry and free from fat. Mask off areas not to be painted. Before use, shake the can vigorously for 3 minutes. Test spray to check colour-matching. The spray distance should be approx. 20-30 cm. Spray several thin cross-coats in 3 - 5 minute intervals. Do not spray over synthetic paints!



3 min



approx. 20-30 cm



20°C=120 min



5 sec

Environmentally compatible: Le'Mix Pty Ltd is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse"

DISCLAIMER OF LIABILITY

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Le'Mix Pty Ltd is not responsible for any misuse or mishandling and therefore will not accept any liability.

For any further technical questions call Le'Mix + 61 02 97084959 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

Refer to SDS for all safety, handling, transport and chemical ingredients