

# Le'Mix

SURFACE COATING SOLUTIONS

## 2K PROTECTIVE TEXTURE COATING

IMPACT, SCRATCH, CHIP, CORROSION, WATER, CHEMICAL AND UV RESISTANT.

Le'Mix 2K Protective Texture Coating is a fast dry coating suitable for interior or exterior protective barrier coat for all types of surfaces, inclusive and not limited to automotive, industrial and marine.

*Guranteed to outperform all other comparable products*

### Properties

- **BLACK or TINTABLE**
- Excellent and reliable application properties
- Fast drying, can be airdried or low baked
- High solids with excellent filling properties
- Excellent gloss and consistant appearance
- Good vertical stability (sag resistance)
- Excellent adhesion
- Corrosion, impact, scratch and chip resistance
- Recoated with solvent and waterborne paints
- Excellent chemicals and stain resistance
- Excellent UV resistance

### Pot Life

Temp:	10 c	20 c	40 c
Time:	3 hrs	2 hrs	1 hrs

### Application

Flash time between coats:	30 min
Flash time before baking:	30 min
Recommended dry film thickness:	300 mic

### Drying

	Dust dry	to handle	hard dry
Air dry at 25c	2 hrs	6 hrs	overnight
Drying at 60c	60min	60min	60min

